

PRODUCT NO. 3292-240060

DOTLUX LED luminaire insert LINEAselect 1437mm 25-75W 4000K dimmable 1-10V 60°



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection and power adjustment via DIP switch on the power supply unit
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price-performance ratio
- Long service life thanks to oversized cooling
- Suitable for central battery

Adjustable output thanks to POWERselect:

- 14100@ 75W
- 12250@ 65W
- 10250@ 55W
- 8500@ 45W
- 7850@ 40W
- 6800@ 35W
- 5800@ 30W
- 4750@ 25W

SUCCESSION ARTICLE	-	BEAM ANGLE	60
WEIGHT IN KG	1.87	PROTECTION CLASS (IP)	IP40
POWER CONSUMPTION IN WATTS	25-75	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	max.14100	INPUT VOLTAGE	186 - 240 AC/DC
LUMEN PER WATT	188-190	SERVICE LIFE	approx. 100,000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 83
		POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	188-190
		PROTECTION CLASS	I
		HOUSING COLOUR	white
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	7
		L80/B10	100000
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	100000
Dimensions			
length:	1437mm		
width:	65mm		
height:	45mm		

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	200000
ETIM GROUP IDENTIFICATION NUMBER	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING 1-10 V	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
LIFETIME L70/B50 AT 25°C	200000
LIFETIME L90/B10 AT 25°C	50000
PULSE DURATION IN µs	0
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	B
COLOUR OF LIGHT ADJUSTABLE	No