

PRODUCT NO. 3293-240180-DALI

DOTLUX LED luminaire insert LINEAselect 1437mm 25-80W 4000K dimmable DALI 120°



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection and power adjustment via DIP switch on the power supply unit
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price-performance ratio
- Long service life thanks to oversized cooling
- Suitable for central battery

Adjustable output thanks to POWERselect:

- 12300@ 78W
- 10900@ 70W
- 9400@ 59W
- 7850@ 47W
- 7200@ 43W
- 6100@ 37W
- 5250@ 32W
- 4300@ 26W

SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	3293-040180-DALI	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	1.66	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	25-80	INPUT VOLTAGE	186 - 240 AC/DC
NET LUMINOUS FLUX IN LUMENS	max.12300	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	158-165	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 83
		POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	158-165
		HOUSING COLOUR	white
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	7
		L80/B10	75750
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	75750
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	150000
		ETIM GROUP IDENTIFICATION NUMBER	EC002892

Dimensions

length: 1437mm
width: 65mm
height: 59mm

MATERIAL COVER	Plastic matt/satinized
DIMMING DALI	Yes
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
LIFETIME L70/B50 AT 25°C	150000
LIFETIME L90/B10 AT 25°C	37500
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	B
COLOUR OF LIGHT ADJUSTABLE	No