

PRODUCT NO. 4934-950

Light management system LED power supply unit 38Watt 950mA DALI DT8 dimmable



PROTECTION CLASS (IP)

IFTTT SUPPORT AVAILABLE

PULSE DURATION IN µS

BEG FUNDING







to the product page



- Independent dimmable two-channel DALI DT8 LED driver
- Dimming range from 1 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- colorSWITCH setting the color temperature via push-button
- Tunable White applications

SUCCESSION ARTICLE

| PREDECESSOR ARTICLE | 4184-900 | INPUT VOLTAGE | 176 - 240 V AC/DC |
|---------------------|----------|----------------------------------|-------------------|
| | | OUTPUT CURRENT IN A | 0,95 |
| WEIGHT IN KG | 0.241 | INRUSH CURRENT IN A | 26.4 |
| | | TC TEMPERATURE IN °C | 75 |
| | | OUTPUT VOLTAGE | 20 - 40 DC |
| | | INPUT VOLTAGE SPAN | 198-264 AC |
| Dimensions | | WARRANTY IN YEARS | 5 |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 198-264 AC |
| length: 215mm | | ETIM GROUP IDENTIFICATION NUMBER | EC002710 |
| width: 70mm | | DIMMING DALI | Yes |
| height: 31mm | | NO DIM FUNCTION | No |
| | | COMPATIBLE WITH CASAMBI | No |
| | | COMPATIBLE WITH APPLE HOMEKIT | No |
| | | COMPATIBLE WITH GOOGLE ASSISTANT | No |
| | | COMPATIBLE WITH AMAZON ALEXA | No |
| | | | |

No

224

Only relevant in Germany

IP20