

PRODUCT NO. 4941-700

Light management system LED power supply unit 38Watt 700mA CASAMBI dimmable



to the product page

- Independent dimmable dual-channel CASAMBI LED driver
- Automatically establishes a wireless communication network with up to 127 nodes
- Dimming range from 1 - 100% with amplitude dimming
- Suitable for DC input voltage and emergency lighting systems in accordance with EN50172
- Strain relief with the option of through-wiring
- Tunable White applications

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.25	INPUT VOLTAGE	176 - 240 V AC/DC
		OUTPUT CURRENT IN A	0,7
		INRUSH CURRENT IN A	26.4
		TC TEMPERATURE IN °C	75
Dimensions		SUITED FOR EMERGENCY LIGHTING	No
length: 215mm		OUTPUT VOLTAGE	20 - 50 DC
width: 70mm		INPUT VOLTAGE SPAN	198-264 AC
height: 31mm		WARRANTY IN YEARS	5
diameter: 75mm		DIMMING WITHOUT DIMMER	No
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
		ETIM GROUP IDENTIFICATION NUMBER	ECO02710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	Yes
		DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
MODEL	Other
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	224
BEG FUNDING	Only relevant in Germany