


PRODUCT NO. 4989

CASAMBI LED power supply 1-38Watt 300-1050mA dimmable



to the product page

 Die Besonderheit dieses Konstantstromtreibers:
Neben dem integrierten CASAMBI-Funkempfänger verfügt dieses EVG über Amplitudendimmung und erhebt durch absolut flickerfreies Licht. (Keine PWM). Der Dimmbereich liegt dabei zwischen 1% - 100%.

- Control via smartphone via CASAMBI APP
- Integrated connection for manual dimming via push button
- Amplitude dimming for absolutely flicker-free light at any dimming level 1-100%.
- MADE in EU

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.144	INPUT VOLTAGE	176 - 240 V AC/DC
		OUTPUT CURRENT IN A	0,3-1,05
		POWER FACTOR	0,99
		INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	80
Dimensions		PROTECTION CLASS	II
length: 147mm		SUITED FOR EMERGENCY LIGHTING	No
width: 44mm		WARRANTY IN YEARS	5
height: 30mm		DIMMING WITHOUT DIMMER	No
		ETIM GROUP IDENTIFICATION NUMBER	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	Yes
		DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
SUITABLE FOR EMERGENCY LIGHTING	No
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
MODEL	Other
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR DC-VOLTAGE (PRIMARY SIDE)	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany